

MATERIAL SAFETY DATA SHEET

Prepared August 15, 2002

MANUFACTURER:

EASIWAY SYSTEMS, INC.
 540 S River Street
 P.O. Box 70
 Delano, MN 55328
 Business Phone: 1-612-972-6306
 Emergency Phone: 1-800-424-9300

IMPORTANT:

Read this MSDS before handling and disposing of this product and pass this information on to employees, customers and users of this product.

SECTION I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: EASISOLV 120
 PRODUCT USE: SOLVENT CLEANER
 CLASS: Organic Solvent mixture
 DOT SHIPPING NAME: Cleaning Compound, N.O.I.
 Not DOT regulated for ground transportation.
 Do not ship via air transport.

HMIS

Health: 1
 Flammability: 2
 Reactivity: 0
 Personal Protection: B

SECTION II - COMPONENTS

Isobutyl isobutyrate

**CAS
#**
97-95-8

**OSHA
PEL**
None estab.

**ACGIH
TLV**
None estab.

None of the ingredients in this product are on the OSHA Hazardous Substance List or any individual State Hazardous Substance List.

Complies with SCAQMD Rules 443.1 and 1171.
 SARA - None of the ingredients are SARA reportable.

SECTION III - PHYSICAL DATA

APPEARANCE AND ODOR: Clear, colorless liquid - mild odor.
 BOILING POINT: 150°C
 SPECIFIC GRAVITY: 0.95 @ 20°C.
 VAPOR PRESSURE: VOC composite Partial Pressure 3.6mm Hg @ 20°C.
 VAPOR DENSITY: Heavier than air.
 VOC: 950 grams per liter by EPA Method 24.
 EVAPORATION RATE: 0.35 (n-butylacetate = 1)
 pH: Neutral

SECTION IV - FIRE OR EXPLOSION HAZARD

FLASHPOINT: 118°F Setaflash
 EXTINGUISHING MEDIA: Universal type foam, CO₂ or dry.
 UNUSUAL FIRE & EXPLOSION HAZARDS: This material is combustible and may be ignited by heat or flame.
 FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

SECTION V - REACTIVITY DATA

STABILITY: Stable under normal conditions of storage and handling. Avoid heat, sparks and open flames.
 INCOMPATIBILITY: Oxidizing or reducing agents.
 HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARD DATA

ROUTE OF ENTRY: Inhalation, skin absorption and ingestion.

EFFECTS OF ACUTE EXPOSURE:

EYE CONTACT: This material may cause eye irritation. Direct contact with the liquid or exposure to its vapors or mists may cause burning, tearing and redness.

SKIN CONTACT: This material may cause skin irritation. Prolonged or repeated exposure to this material may cause redness, burning, and drying and cracking of the skin. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

INHALATION (BREATHING): Breathing high concentrations of vapors or mists may cause: irritation of the nose and throat. Signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination and fatigue). Respiratory symptoms associated with pre-existing lung disorders (e.g., asthma-like conditions) may be aggravated by exposure to this material.

EFFECTS OF CHRONIC EXPOSURE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as solvent or painter's syndrome).

CARCINOGENICITY: No

TERATOGENICITY: No

REPRODUCTIVE TOXICITY: No

MUTAGENICITY: No

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

PERSONAL PROTECTIVE EQUIPMENT: Wear safety glasses or goggles and nitrile gloves when handling. Keep containers closed when not in use. Provide adequate ventilation in work area. A respirator should be worn if needed.

LEAK AND SPILLS PROCEDURE: Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. If spill is indoors, ventilate area of spill. A universal type foam may be used to suppress vapors. Keep out of drains, sewers or waterways. Use sand or other inert material to dam and contain spill. Do not flush area with water. For small spills, use absorbent pads.

WASTE DISPOSAL: Dispose of in accordance with local, county, state and federal regulations.

Do not weld, cut, braze or drill drums that are empty.

SECTION VIII - FIRST AID MEASURES

EYE CONTACT: If irritation or redness from exposure to vapors develops, move victim away from exposure and into fresh air. If irritation or redness persists, seek medical attention. For direct contact, flush the affected eye(s) with clean water. Seek medical attention.

SKIN CONTACT: Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

INHALATION (BREATHING): If symptoms of exposure develop (See Section VI), move victim away from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, artificial respiration should be administered by qualified personnel. Seek immediate medical attention.

INGESTION (SWALLOWING): Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious, place on the left side with head down. If possible, do not leave victim unattended. Seek medical attention.

SECTION IX - ADDITIONAL INFORMATION

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. THE CONDITION OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.