

Material Safety Data Sheet

Quick Identifier: Thinner 100-VR-1279

RUCO Druckfarben
A.M. Ramp & Co. GmbH
D-65814 Eppstein/Ts.

Hazard Ratings: Health 1
Flammability 2
Reactivity 0

Section I

Distributors: ITW Imtran. **Information:** Tel: +49-6198-3040 (RUCO)
Address: 39 Shelley Road Tel: 978-372-3443 (Imtran)
City/State/Zip: Haverhill, MA 01835 Fax: 978-372-9817

Person Responsible for Preparation: Dr. H. Nitschke **Date Prepared:** Sept. 1996

Section II Hazardous Ingredients

Hazardous Component(s) (Chemical & Common name(s))	OSHA PEL (ppm)	ACGIH TLV (ppm)	Other Exposure Limits (ppm)	Range (weight-%)	CAS-No.
---	-------------------	--------------------	--------------------------------	---------------------	---------

The product does not contain any ingredients being classified toxic according to EU regulations

Section III Physical & Chemical Characteristics

Boiling Point 158 °C (316 °F)	Specific Gravity (H₂O = 1) 0.94	Vapor Pressure (mbar) 0.2
---	--	-------------------------------------

Vapor Density	Heavier than air (3-4)	VOC (ingredients with vapor pressure > 0.1 mbar) 940 g/l
----------------------	------------------------	---

Solubility In Water insoluble	Reactivity In Water none
---	------------------------------------

Appearance & Odor	Clear liquid with odor of organic solvents	Melting Point Unknown
------------------------------	--	------------------------------

Section IV Fire & Explosion Data

Flash Point 54 °C (129 °F)	Method Used Closed cup	Flammable Limits In Air % by Volume	LEL (Lower) 1.0	UEL (Upper) 9.8
--------------------------------------	----------------------------------	---	---------------------------	---------------------------

Auto-Ignition Temperature 335 °C (635 °F)	Extinguishing Media Chemical powder, foam, carbon dioxide
---	---

Special Fire Fighting Procedures	Foam in large quantities. Cool endangered containers with water.
---	--

Unusual Fire & Explosion Hazards	Heat, sparks, open fire or static electricity may cause combustion of the product. When pouring liquid from one container to another, keep both containers well grounded.
---	---

